



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 Ω /km
芯线 PVC 材质							
ANM09.008.01.022AB	UL10572	1000V	1X22AWG	22/0.14	4.2	23.73	55.4 Ω /km
ANM09.008.01.021AB	UL10572	1000V	1X21AWG	27/0.14	4.3	25.42	43.6 Ω /km
ANM09.008.01.020AB	UL10572	1000V	1X20AWG	34/0.14	4.4	27.32	34.6 Ω /km
ANM09.008.01.019AB	UL10572	1000V	1X19AWG	43/0.14	4.5	29.56	27.4 Ω /km
ANM09.008.01.018AB	UL10572	1000V	1X18AWG	29/0.19	4.6	32.23	21.8 Ω /km
ANM09.008.01.017AB	UL10572	1000V	1X17AWG	37/0.19	4.8	36.14	17.3 Ω /km
ANM09.008.01.016AB	UL10572	1000V	1X16AWG	27/0.25	5.1	42.01	13.7 Ω /km
ANM09.008.01.015AB	UL10572	1000V	1X15AWG	34/0.25	5.3	47.35	10.9 Ω /km
ANM09.008.01.014AB	UL10572	1000V	1X14AWG	43/0.25	5.5	53.48	8.62 Ω /km
ANM09.008.01.013AB	UL10572	1000V	1X13AWG	54/0.25	5.8	61.73	6.82 Ω /km
ANM09.008.01.012AB	UL10572	1000V	1X12AWG	68/0.25	6.2	73.51	5.43 Ω /km
ANM09.008.01.011AB	UL10572	1000V	1X11AWG	85/0.25	6.6	85.97	4.30 Ω /km
ANM09.008.01.010AB	UL10572	1000V	1X10AWG	108/0.25	7.2	102.87	3.409 Ω /km
ANM09.008.01.009AB	UL10572	1000V	1X9AWG	136/0.25	7.9	127.14	2.705 Ω /km
ANM09.008.01.008AB	UL10572	1000V	1X8AWG	171/0.25	8.3	149.27	2.144 Ω /km
ANM09.008.01.007AB	UL10572	1000V	1X7AWG	84/0.4	8.7	175.95	1.700 Ω /km
ANM09.008.01.006AB	UL10572	1000V	1X6AWG	106/0.4	9.4	211.7	1.348 Ω /km
ANM09.008.01.005AB	UL10572	1000V	1X5AWG	134/0.4	10	253.97	1.070 Ω /km
ANM09.008.01.004AB	UL10572	1000V	1X4AWG	169/0.4	11.3	322.25	0.8481 Ω /km
ANM09.008.01.003AB	UL10572	1000V	1X3AWG	213/0.4	12.1	388.87	0.6727 Ω /km
ANM09.008.01.002AB	UL10572	1000V	1X2AWG	268/0.4	13	471.52	0.5335 Ω /km
ANM09.008.01.001AB	UL10572	1000V	1X1AWG	338/0.4	15.3	622.01	0.4230 Ω /km
ANM09.008.01.1/0AB	UL10572	1000V	1X1/0AWG	426/0.4	16.6	756.79	0.3354 Ω /km
ANM09.008.01.2/0AB	UL10572	1000V	1X2/0AWG	537/0.4	17.9	921.23	0.2660 Ω /km
ANM09.008.01.3/0AB	UL10572	1000V	1X3/0AWG	677/0.4	19.2	1123.71	0.2110 Ω /km
ANM09.008.01.4/0AB	UL10572	1000V	1X4/0AWG	854/0.4	20.8	1378.9	0.1673 Ω /km
ANM09.008.01.250kB	UL10572	1000V	1X250Kcmil	1007/0.4	23.9	1695	0.1416 Ω /km
ANM09.008.01.300kB	UL10572	1000V	1X300Kcmil	1184/0.4	25	1976.3	0.1180 Ω /km
ANM09.008.01.350kB	UL10572	1000V	1X350Kcmil	1406/0.4	26.5	2264.8	0.1011 Ω /km
ANM09.008.01.400kB	UL10572	1000V	1X400Kcmil	1628/0.4	28	2563.9	0.08851 Ω /km
ANM09.008.01.450kB	UL10572	1000V	1X450Kcmil	1830/0.4	29.2	2846.9	0.07867 Ω /km
ANM09.008.01.500kB	UL10572	1000V	1X500Kcmil	2013/0.4	30.2	3126.3	0.07080 Ω /km
物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 Ω /km
芯线 XLPE 材质							
ANM09.009.01.022AB	UL10572	1000V	1X22AWG	22/0.14	5	32.53	55.4 Ω /km
ANM09.009.01.021AB	UL10572	1000V	1X21AWG	27/0.14	5.1	34.32	43.6 Ω /km
ANM09.009.01.020AB	UL10572	1000V	1X20AWG	34/0.14	5.2	36.52	34.6 Ω /km
ANM09.009.01.019AB	UL10572	1000V	1X19AWG	43/0.14	5.3	38.96	27.4 Ω /km
ANM09.009.01.018AB	UL10572	1000V	1X18AWG	29/0.19	5.4	41.63	21.8 Ω /km
ANM09.009.01.017AB	UL10572	1000V	1X17AWG	37/0.19	5.6	45.94	17.3 Ω /km



ANM09.009.01.016AB	UL10572	1000V	1X16AWG	27/0.25	5.7	49.71	13.7 Ω/km
ANM09.009.01.015AB	UL10572	1000V	1X15AWG	34/0.25	5.9	55.25	10.9 Ω/km
ANM09.009.01.014AB	UL10572	1000V	1X14AWG	43/0.25	6.1	61.78	8.62 Ω/km
ANM09.009.01.013AB	UL10572	1000V	1X13AWG	54/0.25	6.4	70.43	6.82 Ω/km
ANM09.009.01.012AB	UL10572	1000V	1X12AWG	68/0.25	6.6	79.51	5.43 Ω/km
ANM09.009.01.011AB	UL10572	1000V	1X11AWG	85/0.25	7	92.47	4.30 Ω/km
ANM09.009.01.010AB	UL10572	1000V	1X10AWG	108/0.25	7.6	109.87	3.409 Ω/km
ANM09.009.01.009AB	UL10572	1000V	1X9AWG	136/0.25	7.9	127.14	2.705 Ω/km
ANM09.009.01.008AB	UL10572	1000V	1X8AWG	171/0.25	9.1	165.77	2.144 Ω/km
ANM09.009.01.007AB	UL10572	1000V	1X7AWG	84/0.4	9.5	193.25	1.700 Ω/km
ANM09.009.01.006AB	UL10572	1000V	1X6AWG	106/0.4	10.2	230.2	1.348 Ω/km
ANM09.009.01.005AB	UL10572	1000V	1X5AWG	134/0.4	10.8	273.57	1.070 Ω/km
ANM09.009.01.004AB	UL10572	1000V	1X4AWG	169/0.4	11.5	327.55	0.8481 Ω/km
ANM09.009.01.003AB	UL10572	1000V	1X3AWG	213/0.4	12.3	394.77	0.6727 Ω/km
ANM09.009.01.002AB	UL10572	1000V	1X2AWG	268/0.4	13.2	477.82	0.5335 Ω/km
ANM09.009.01.001AB	UL10572	1000V	1X1AWG	338/0.4	14.5	593.81	0.4230 Ω/km
ANM09.009.01.1/0AB	UL10572	1000V	1X1/0AWG	426/0.4	15.8	726.09	0.3354 Ω/km
ANM09.009.01.2/0AB	UL10572	1000V	1X2/0AWG	537/0.4	17.1	888.03	0.2660 Ω/km
ANM09.009.01.3/0AB	UL10572	1000V	1X3/0AWG	677/0.4	18.4	1088.11	0.2110 Ω/km
ANM09.009.01.4/0AB	UL10572	1000V	1X4/0AWG	854/0.4	21	1388.8	0.1673 Ω/km
ANM09.009.01.250KB	UL10572	1000V	1X250Kcmil	1007/0.4	23.1	1650.5	0.1416 Ω/km
ANM09.009.01.300KB	UL10572	1000V	1X300Kcmil	1184/0.4	24.2	1929.7	0.1180 Ω/km
ANM09.009.01.350KB	UL10572	1000V	1X350Kcmil	1406/0.4	25.7	2215.3	0.1011 Ω/km
ANM09.009.01.400KB	UL10572	1000V	1X400Kcmil	1628/0.4	27.2	2511.5	0.08851 Ω/km
ANM09.009.01.450KB	UL10572	1000V	1X450Kcmil	1830/0.4	28.4	2792.3	0.07867 Ω/km
ANM09.009.01.500KB	UL10572	1000V	1X500Kcmil	2013/0.4	30.4	3140.6	0.07080 Ω/km