



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 Ω /km
芯线 PVC 材质							
ANM09.010.01.022AB	UL10660	1000V	1X22AWG	22/0.14	4.4	25.73	55.4 Ω /km
ANM09.010.01.021AB	UL10660	1000V	1X21AWG	27/0.14	4.5	27.52	43.6 Ω /km
ANM09.010.01.020AB	UL10660	1000V	1X20AWG	34/0.14	4.6	29.52	34.6 Ω /km
ANM09.010.01.019AB	UL10660	1000V	1X19AWG	43/0.14	4.7	31.76	27.4 Ω /km
ANM09.010.01.018AB	UL10660	1000V	1X18AWG	29/0.19	4.8	34.43	21.8 Ω /km
ANM09.010.01.017AB	UL10660	1000V	1X17AWG	37/0.19	5	38.44	17.3 Ω /km
ANM09.010.01.016AB	UL10660	1000V	1X16AWG	27/0.25	5.3	44.51	13.7 Ω /km
ANM09.010.01.015AB	UL10660	1000V	1X15AWG	34/0.25	5.5	49.85	10.9 Ω /km
ANM09.010.01.014AB	UL10660	1000V	1X14AWG	43/0.25	5.7	56.08	8.62 Ω /km
ANM09.010.01.013AB	UL10660	1000V	1X13AWG	54/0.25	6	64.53	6.82 Ω /km
ANM09.010.01.012AB	UL10660	1000V	1X12AWG	68/0.25	6.4	76.51	5.43 Ω /km
ANM09.010.01.011AB	UL10660	1000V	1X11AWG	85/0.25	6.8	89.17	4.30 Ω /km
ANM09.010.01.010AB	UL10660	1000V	1X10AWG	108/0.25	7.4	106.27	3.409 Ω /km
ANM09.010.01.009AB	UL10660	1000V	1X9AWG	136/0.25	8.1	130.94	2.705 Ω /km
ANM09.010.01.008AB	UL10660	1000V	1X8AWG	171/0.25	8.5	153.27	2.144 Ω /km
ANM09.010.01.007AB	UL10660	1000V	1X7AWG	84/0.4	8.9	180.15	1.700 Ω /km
ANM09.010.01.006AB	UL10660	1000V	1X6AWG	106/0.4	9.6	216.2	1.348 Ω /km
ANM09.010.01.005AB	UL10660	1000V	1X5AWG	134/0.4	10.2	258.77	1.070 Ω /km
ANM09.010.01.004AB	UL10660	1000V	1X4AWG	169/0.4	11.5	327.65	0.8481 Ω /km
ANM09.010.01.003AB	UL10660	1000V	1X3AWG	213/0.4	12.3	394.67	0.6727 Ω /km
ANM09.010.01.002AB	UL10660	1000V	1X2AWG	268/0.4	13.2	477.72	0.5335 Ω /km
ANM09.010.01.001AB	UL10660	1000V	1X1AWG	338/0.4	15.5	629.31	0.4230 Ω /km
ANM09.010.01.1/0AB	UL10660	1000V	1X1/0AWG	426/0.4	16.8	764.69	0.3354 Ω /km
ANM09.010.01.2/0AB	UL10660	1000V	1X2/0AWG	537/0.4	18.1	929.73	0.2660 Ω /km
ANM09.010.01.3/0AB	UL10660	1000V	1X3/0AWG	677/0.4	19.4	1132.81	0.2110 Ω /km
ANM09.010.01.4/0AB	UL10660	1000V	1X4/0AWG	854/0.4	21	1388.8	0.1673 Ω /km
ANM09.010.01.250kB	UL10660	1000V	1X250Kcmil	1007/0.4	25.3	1776.6	0.1416 Ω /km
ANM09.010.01.300kB	UL10660	1000V	1X300Kcmil	1184/0.4	26.4	2061.5	0.1180 Ω /km
ANM09.010.01.350kB	UL10660	1000V	1X350Kcmil	1406/0.4	27.9	2355	0.1011 Ω /km
ANM09.010.01.400kB	UL10660	1000V	1X400Kcmil	1628/0.4	29.4	2659	0.08851 Ω /km
ANM09.010.01.450kB	UL10660	1000V	1X450Kcmil	1830/0.4	30.6	2946	0.07867 Ω /km
ANM09.010.01.500kB	UL10660	1000V	1X500Kcmil	2013/0.4	31.6	3228.8	0.07080 Ω /km
物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 Ω /km
芯线 XLPE 材质							
ANM09.011.01.022AB	UL10660	1000V	1X22AWG	22/0.14	5.2	34.93	55.4 Ω /km
ANM09.011.01.021AB	UL10660	1000V	1X21AWG	27/0.14	5.3	36.82	43.6 Ω /km
ANM09.011.01.020AB	UL10660	1000V	1X20AWG	34/0.14	5.4	39.02	34.6 Ω /km
ANM09.011.01.019AB	UL10660	1000V	1X19AWG	43/0.14	5.5	41.46	27.4 Ω /km
ANM09.011.01.018AB	UL10660	1000V	1X18AWG	29/0.19	5.6	44.23	21.8 Ω /km
ANM09.011.01.017AB	UL10660	1000V	1X17AWG	37/0.19	5.8	48.64	17.3 Ω /km



ANM09.011.01.016AB	UL10660	1000V	1X16AWG	27/0.25	5.9	52.51	13.7 Ω/km
ANM09.011.01.015AB	UL10660	1000V	1X15AWG	34/0.25	6.1	58.05	10.9 Ω/km
ANM09.011.01.014AB	UL10660	1000V	1X14AWG	43/0.25	6.3	64.68	8.62 Ω/km
ANM09.011.01.013AB	UL10660	1000V	1X13AWG	54/0.25	6.6	73.53	6.82 Ω/km
ANM09.011.01.012AB	UL10660	1000V	1X12AWG	68/0.25	6.8	82.71	5.43 Ω/km
ANM09.011.01.011AB	UL10660	1000V	1X11AWG	85/0.25	7.2	95.87	4.30 Ω/km
ANM09.011.01.010AB	UL10660	1000V	1X10AWG	108/0.25	7.8	113.57	3.409 Ω/km
ANM09.011.01.009AB	UL10660	1000V	1X9AWG	136/0.25	8.1	130.94	2.705 Ω/km
ANM09.011.01.008AB	UL10660	1000V	1X8AWG	171/0.25	9.3	170.07	2.144 Ω/km
ANM09.011.01.007AB	UL10660	1000V	1X7AWG	84/0.4	9.7	197.85	1.700 Ω/km
ANM09.011.01.006AB	UL10660	1000V	1X6AWG	106/0.4	10.4	235.1	1.348 Ω/km
ANM09.011.01.005AB	UL10660	1000V	1X5AWG	134/0.4	11	278.77	1.070 Ω/km
ANM09.011.01.004AB	UL10660	1000V	1X4AWG	169/0.4	11.7	333.05	0.8481 Ω/km
ANM09.011.01.003AB	UL10660	1000V	1X3AWG	213/0.4	12.5	400.57	0.6727 Ω/km
ANM09.011.01.002AB	UL10660	1000V	1X2AWG	268/0.4	13.4	484.12	0.5335 Ω/km
ANM09.011.01.001AB	UL10660	1000V	1X1AWG	338/0.4	15.7	636.71	0.4230 Ω/km
ANM09.011.01.1/0AB	UL10660	1000V	1X1/0AWG	426/0.4	17	772.69	0.3354 Ω/km
ANM09.011.01.2/0AB	UL10660	1000V	1X2/0AWG	537/0.4	18.3	938.43	0.2660 Ω/km
ANM09.011.01.3/0AB	UL10660	1000V	1X3/0AWG	677/0.4	19.6	1142.11	0.2110 Ω/km
ANM09.011.01.4/0AB	UL10660	1000V	1X4/0AWG	854/0.4	21.2	1398.8	0.1673 Ω/km
ANM09.011.01.250kB	UL10660	1000V	1X250Kcmil	1007/0.4	25.5	1788.6	0.1416 Ω/km
ANM09.011.01.300kB	UL10660	1000V	1X300Kcmil	1184/0.4	26.6	2074.1	0.1180 Ω/km
ANM09.011.01.350kB	UL10660	1000V	1X350Kcmil	1406/0.4	28.1	2368.3	0.1011 Ω/km
ANM09.011.01.400kB	UL10660	1000V	1X400Kcmil	1628/0.4	29.6	2673	0.08851 Ω/km
ANM09.011.01.450kB	UL10660	1000V	1X450Kcmil	1830/0.4	30.8	2960.6	0.07867 Ω/km
ANM09.011.01.500kB	UL10660	1000V	1X500Kcmil	2013/0.4	31.8	3243.7	0.07080 Ω/km