



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 Ω /km
ANO10.001.01.000.75B	H05RN-F	300/500V	1X0.75	27/0.19	4.5	30.55	19.5 Ω /km
ANO10.001.01.001.00B	H05RN-F	300/500V	1X1	35/0.19	4.7	34.8	13.3 Ω /km
ANO10.001.01.001.50B	H05RN-F	300/500V	1X1.5	31/0.25	5	42.3	10.64 Ω /km
ANO10.001.02.000.75B	H05RN-F	300/500V	2X0.75	27/0.19	6.4	60.95	19.5 Ω /km
ANO10.001.02.001.00B	H05RN-F	300/500V	2X1	35/0.19	7.2	77.8	13.3 Ω /km
ANO10.001.02.001.50B	H05RN-F	300/500V	2X1.5	31/0.25	8.8	116.2	10.64 Ω /km
ANO10.001.02.002.50B	H05RN-F	300/500V	2X2.5	51/0.25	10.4	168.2	4.95 Ω /km
ANO10.001.02.004.00B	H05RN-F	300/500V	2X4	82/0.25	12.1	238.1	3.30 Ω /km
ANO10.001.03.000.75B	H05RN-F	300/500V	3X0.75	27/0.19	7.2	79.45	19.5 Ω /km
ANO10.001.03.001.00B	H05RN-F	300/500V	3X1	35/0.19	7.6	92.2	13.3 Ω /km
ANO10.001.03.001.50B	H05RN-F	300/500V	3X1.5	31/0.25	9.3	137.9	10.64 Ω /km
ANO10.001.03.002.50B	H05RN-F	300/500V	3X2.5	51/0.25	11.2	206.9	4.95 Ω /km
ANO10.001.03.004.00B	H05RN-F	300/500V	3X4	82/0.25	12.9	291.4	3.30 Ω /km
ANO10.001.03.006.00B	H05RN-F	300/500V	3X6	123/0.25	14.6	393.3	1.91 Ω /km
ANO10.001.04.000.75B	H05RN-F	300/500V	4X0.75	27/0.19	7.8	95.95	19.5 Ω /km
ANO10.001.04.001.00B	H05RN-F	300/500V	4X1	35/0.19	8.3	112.9	13.3 Ω /km
ANO10.001.04.001.50B	H05RN-F	300/500V	4X1.5	31/0.25	10.4	174.8	10.64 Ω /km
ANO10.001.04.002.50B	H05RN-F	300/500V	4X2.5	51/0.25	12.4	259	4.95 Ω /km
ANO10.001.04.004.00B	H05RN-F	300/500V	4X4	82/0.25	14.3	366.4	3.30 Ω /km
ANO10.001.04.006.00B	H05RN-F	300/500V	4X6	123/0.25	16.1	492.4	1.91 Ω /km
ANO10.001.05.000.75B	H05RN-F	300/500V	5X0.75	27/0.19	8.7	119.15	19.5 Ω /km
ANO10.001.05.001.00B	H05RN-F	300/500V	5X1	35/0.19	9.2	139	13.3 Ω /km
ANO10.001.05.001.50B	H05RN-F	300/500V	5X1.5	31/0.25	11.4	211.8	10.64 Ω /km
ANO10.001.05.002.50B	H05RN-F	300/500V	5X2.5	51/0.25	13.7	317.8	4.95 Ω /km
ANO10.001.05.004.00B	H05RN-F	300/500V	5X4	82/0.25	15.8	449.8	3.30 Ω /km