



物料编号	型号	额定电压	规格	导体结构	电缆近似 外径 mm	近似重量 kg/km	导体电阻 Ω /km
AN002.014.01.000.50B	SiF	300/500V	1X0.5	18/0.19	2.25	8.83	39 Ω /km
AN002.014.01.000.75B	SiF	300/500V	1X0.75	27/0.19	2.45	11.74	26 Ω /km
AN002.014.01.001.00B	SiF	300/500V	1X1	35/0.19	2.65	14.64	19.5 Ω /km
AN002.014.01.001.50B	SiF	300/500V	1X1.5	31/0.25	2.95	20.18	13.3 Ω /km
AN002.014.01.002.50B	SiF	300/500V	1X2.5	51/0.25	3.65	32.55	7.98 Ω /km
AN002.014.01.004.00B	SiF	300/500V	1X4	82/0.25	4.4	50.18	4.95 Ω /km
AN002.014.01.006.00B	SiF	300/500V	1X6	123/0.25	5.2	73.47	3.3 Ω /km
AN002.014.01.010.00B	SiF	300/500V	1X10	77/0.4	6.5	118.57	1.91 Ω /km
AN002.014.01.016.00B	SiF	300/500V	1X16	126/0.4	7.8	180.66	1.21 Ω /km
AN002.014.01.025.00B	SiF	300/500V	1X25	189/0.4	9.5	279.74	0.78 Ω /km
AN002.014.01.035.00B	SiF	300/500V	1X35	266/0.4	10.9	381.21	0.554 Ω /km
AN002.014.01.050.00B	SiF	300/500V	1X50	380/0.4	12.6	536.48	0.386 Ω /km
AN002.014.01.070.00B	SiF	300/500V	1X70	532/0.4	14.6	742.31	0.272 Ω /km
AN002.014.01.095.00B	SiF	300/500V	1X95	722/0.4	17	1005.22	0.206 Ω /km
AN002.014.01.120.00B	SiF	300/500V	1X120	925/0.4	18.8	1254.24	0.161 Ω /km
AN002.014.01.150.00B	SiF	300/500V	1X150	1147/0.4	20.5	1549.69	0.129 Ω /km
AN002.014.01.185.00B	SiF	300/500V	1X185	1403/0.4	23.3	1933.65	0.106 Ω /km
AN002.014.01.240.00B	SiF	300/500V	1X240	1830/0.4	27.1	2524.21	0.0801 Ω /km