



频率 FREQ	插入损耗 INSERTION LOSS	近端串音 衰减 NEXT	近端串音 衰减功率 和 PS NEXT	远端衰减 串扰比 ACRF	PS ACRF	回波损耗 RETURN LOSS (dB)	相位延迟 PROP. DELAY (ns/100m)	外来串扰 ALIEN CROSSTALK		
								外部近端串音衰 减功率和 PS ANEXT (dB/100m)	PS AACRN (dB/100m)	衰减外部远端串音 比功率和 PS AACRF (dB/100m)
(MHz)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB)	(ns/100m)	(dB/100m)	(dB/100m)	(dB/100m)
	max	min	min	min	min	min	max	min	min	min
1	2.1	75.3	73.3	71.8	68.8	20	570	74.5	72.4	74.5
4	3.8	66.3	64.3	59.8	56.8	23	552	74.5	70.7	73.7
8	5.3	61.8	59.8	53.7	50.7	24.5	546.7	74.5	69.2	67.6
10	5.9	60.3	58.3	51.8	48.8	25	545.4	74.5	68.6	65.7
16	7.5	57.2	55.2	47.7	44.7	25	543	74.5	67	61.6
20	8.4	55.8	53.8	45.8	42.8	25	542	74.5	66.1	59.7
25	9.4	54.3	52.3	43.8	40.8	24.3	541.2	74.5	65.1	57.7
31.25	10.5	52.9	50.9	41.9	38.9	23.6	540.4	74.5	64	55.8
62.5	14.9	48.4	46.4	35.9	32.9	21.5	538.6	73.1	58.2	49.8
100	19	45.3	43.3	31.8	28.8	20.1	537.6	70	51	45.7
200	27.4	40.8	38.8	25.8	22.8	18	536.9	65.5	38.1	39.7
250	30.8	39.3	37.3	23.8	20.8	17.3	536.5	64	33.2	37.7
300	34	38.1	36.1	22.3	19.3	16.8	536.3	62.8	28.8	36.2
350	36.9	37.1	35.1	20.9	17.9	16.3	536.1	61.8	24.9	34.8
400	39.7	36.3	34.3	19.8	16.8	15.9	535.9	61	21.3	33.7
450	42.3	35.5	33.5	18.7	15.7	15.5	535.8	60.2	17.9	32.6
500	44.8	34.8	32.8	17.8	14.8	15.2	535.6	59.5	14.7	31.7
550	47.2	34.2	32.2	17	14	14.9	--	58.9	11.7	30.9
600	49.5	33.6	31.6	16.2	13.2	14.7	--	58.3	8.8	30.1
650	51.7	33.4	31.1	15.5	12.5	14.4	--	57.8	6.1	29.4
750	56	32.2	30.2	14.3	11.3	14	--	56.9	0.9	28.2