



物料编号	规格	导体结构	外径下限 mm	外径上限 mm	近似重量 kg/km	导体电阻 Ω /km
AN018.002.01.000.50B	1x0.50	18/0.19	2	2.3	8	37.1
AN018.002.01.000.75B	1x0.75	27/0.19	2.2	2.5	11	24.7
AN018.002.01.001.00B	1x1.00	35/0.19	2.4	2.7	15	18.5
AN018.002.01.001.50B	1x1.50	31/0.25	2.7	3	20	12.7
AN018.002.01.002.50B	1x2.50	51/0.25	3.3	3.6	32	7.6
AN018.002.01.004.00B	1x4.00	82/0.25	4	4.4	48	4.71
AN018.002.01.006.00B	1x6.00	123/0.25	4.6	5	68	3.14
AN018.002.01.010.00B	1x10.00	77/0.4	6	6.5	117	1.82
AN018.002.01.016.00B	1x16.00	126/0.4	8	8.3	193	1.16
AN018.002.01.025.00B	1x25.00	189/0.4	10.1	10.4	274	0.7
AN018.002.01.035.00B	1x35.00	266/0.4	11.3	11.6	397	0.5
AN018.002.01.050.00B	1x50.00	380/0.4	13.2	13.5	547	0.3
AN018.002.01.070.00B	1x70.00	532/0.4	15.2	15.5	769	0.2
AN018.002.01.095.00B	1x95.00	722/0.4	17	18	990	0.2