



| 物料编号                 | 型号      | 额定电压     | 规格     | 电缆近似外径<br>mm | 近似重量<br>kg/km | 导体电阻Ω/km    |
|----------------------|---------|----------|--------|--------------|---------------|-------------|
| AN002.005.01.000.50B | H05Z1-K | 300/500V | 1X0.5  | 2.3          | 9.6           | 26.0 Ω/km   |
| AN002.005.01.000.75B | H05Z1-K | 300/500V | 1X0.75 | 2.5          | 12.75         | 19.5 Ω/km   |
| AN002.005.01.001.00B | H05Z1-K | 300/500V | 1X1    | 2.7          | 16            | 13.3 Ω/km   |
| AN002.011.01.001.50B | H07Z1-K | 450/750V | 1X1.5  | 3.2          | 23.4          | 10.64 Ω/km  |
| AN002.011.01.002.50B | H07Z1-K | 450/750V | 1X2.5  | 3.9          | 37.1          | 4.95 Ω/km   |
| AN002.011.01.004.00B | H07Z1-K | 450/750V | 1X4    | 4.4          | 54.7          | 3.30 Ω/km   |
| AN002.011.01.006.00B | H07Z1-K | 450/750V | 1X6    | 5            | 77.9          | 1.91 Ω/km   |
| AN002.011.01.010.00B | H07Z1-K | 450/750V | 1X10   | 6.5          | 129.6         | 1.21 Ω/km   |
| AN002.011.01.016.00B | H07Z1-K | 450/750V | 1X16   | 7.9          | 197.8         | 0.780 Ω/km  |
| AN002.011.01.025.00B | H07Z1-K | 450/750V | 1X25   | 9.6          | 306.4         | 0.554 Ω/km  |
| AN002.011.01.035.00B | H07Z1-K | 450/750V | 1X35   | 11           | 418.1         | 0.386 Ω/km  |
| AN002.011.01.050.00B | H07Z1-K | 450/750V | 1X50   | 12.9         | 594.7         | 0.272 Ω/km  |
| AN002.011.01.070.00B | H07Z1-K | 450/750V | 1X70   | 14.7         | 815.3         | 0.206 Ω/km  |
| AN002.011.01.095.00B | H07Z1-K | 450/750V | 1X95   | 17           | 1104.3        | 0.161 Ω/km  |
| AN002.011.01.120.00B | H07Z1-K | 450/750V | 1X120  | 18.8         | 1378.7        | 0.129 Ω/km  |
| AN002.011.01.150.00B | H07Z1-K | 450/750V | 1X150  | 21.2         | 1723.8        | 0.106 Ω/km  |
| AN002.011.01.185.00B | H07Z1-K | 450/750V | 1X185  | 23.4         | 2125.5        | 0.0801 Ω/km |
| AN002.011.01.240.00B | H07Z1-K | 450/750V | 1X240  | 26.5         | 2749.2        | 0.0641 Ω/km |