



产品结构尺寸

物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻 $\Omega/\text{km}$
AN020.03.01.002.50B	FHLR91XC13X	1000V	1X2.5	51/0.25	4.3	4.9	4.95 $\Omega/\text{km}$
AN020.03.01.004.00B	FHLR91XC13X	1000V	1X4	82/0.25	5.1	7	3.30 $\Omega/\text{km}$
AN020.03.01.006.00B	FHLR91XC13X	1000V	1X6	123/0.25	6.1	9.8	1.91 $\Omega/\text{km}$
AN020.04.01.010.00B	FHLR4GC13X	1000V	1X10	77/0.4	8.1	15.8	1.21 $\Omega/\text{km}$
AN020.04.01.016.00B	FHLR4GC13X	1000V	1X16	126/0.4	9.6	23	0.780 $\Omega/\text{km}$
AN020.04.01.025.00B	FHLR4GC13X	1000V	1X25	189/0.4	11.3	32.8	0.554 $\Omega/\text{km}$
AN020.04.01.035.00B	FHLR4GC13X	1000V	1X35	266/0.4	13.2	44.7	0.386 $\Omega/\text{km}$
AN020.04.01.050.00B	FHLR4GC13X	1000V	1X50	380/0.4	15.2	64.2	0.272 $\Omega/\text{km}$
AN020.04.01.070.00B	FHLR4GC13X	1000V	1X70	532/0.4	17.7	85.8	0.206 $\Omega/\text{km}$
AN020.04.01.095.00B	FHLR4GC13X	1000V	1X95	722/0.4	19.9	115.3	0.161 $\Omega/\text{km}$
AN020.04.01.120.00B	FHLR4GC13X	1000V	1X120	925/0.4	22.9	145.5	0.129 $\Omega/\text{km}$

产品电性能

标称截面	20℃直流电阻	屏蔽转移阻抗
$\text{mm}^2$	ohms/km	$\text{m}\Omega/\text{m}$
2.5	7.98	100
4	4.95	110
6	3.3	70
10	1.91	30
16	1.21	40
25	0.78	40
35	0.554	60
50	0.386	30
70	0.272	30
95	0.206	20
120	0.161	20