



物料编号	型号	规格	额定电压	导体结构	电缆近似 外径 mm	近似重量 kg/km	导体电 阻Ω/km
ANO06.001.03.000.50B	H05VV5-F	3 G0.5	300/500V	18/0.19	7	62.4	39.00
ANO06.001.04.000.50B	H05VV5-F	4 G0.5	300/500V	18/0.19	7.9	68.2	39.00
ANO06.001.05.000.50B	H05VV5-F	5 G0.5	300/500V	18/0.19	8.6	87.1	39.00
ANO06.001.07.000.50B	H05VV5-F	7 G0.5	300/500V	18/0.19	10.4	118.7	39.00
ANO06.001.12.000.50B	H05VV5-F	12 G0.5	300/500V	18/0.19	12.9	198	39.00
ANO06.001.18.000.50B	H05VV5-F	18 G0.5	300/500V	18/0.19	15.3	266.9	39.00
ANO06.001.25.000.50B	H05VV5-F	25 G0.5	300/500V	18/0.19	18.3	380.4	39.00
ANO06.001.34.000.50B	H05VV5-F	34 G0.5	300/500V	18/0.19	21.2	509	39.00
ANO06.001.03.000.75B	H05VV5-F	3 G0.75	300/500V	27/0.19	7.6	75.6	26.00
ANO06.001.04.000.75B	H05VV5-F	4 G0.75	300/500V	27/0.19	8.3	83.9	26.00
ANO06.001.05.000.75B	H05VV5-F	5 G0.75	300/500V	27/0.19	9.3	113.3	26.00
ANO06.001.07.000.75B	H05VV5-F	7 G0.75	300/500V	27/0.19	11.3	145	26.00
ANO06.001.12.000.75B	H05VV5-F	12 G0.75	300/500V	27/0.19	13.7	244.9	26.00
ANO06.001.18.000.75B	H05VV5-F	18 G0.75	300/500V	27/0.19	16.4	327.7	26.00
ANO06.001.25.000.75B	H05VV5-F	25 G0.75	300/500V	27/0.19	19.5	466.4	26.00
ANO06.001.34.000.75B	H05VV5-F	34 G0.75	300/500V	27/0.19	22.6	626.5	26.00
ANO06.001.41.000.75B	H05VV5-F	41 G0.75	300/500V	27/0.19	24.7	748	26.00
ANO06.001.03.001.00B	H05VV5-F	3 G 1.0	300/500V	35/0.19	8	89.3	19.50
ANO06.001.04.001.00B	H05VV5-F	4 G 1.0	300/500V	35/0.19	8.7	98.6	19.50
ANO06.001.05.001.00B	H05VV5-F	5 G 1.0	300/500V	35/0.19	9.8	132.1	19.50
ANO06.001.07.001.00B	H05VV5-F	7 G 1.0	300/500V	35/0.19	11.8	169.3	19.50
ANO06.001.12.001.00B	H05VV5-F	12 G 1.0	300/500V	35/0.19	14.6	285.9	19.50
ANO06.001.18.001.00B	H05VV5-F	18 G 1.0	300/500V	35/0.19	17.2	405.2	19.50
ANO06.001.25.001.00B	H05VV5-F	25 G 1.0	300/500V	35/0.19	20.7	569.5	19.50
ANO06.001.34.001.00B	H05VV5-F	34 G 1.0	300/500V	35/0.19	24	741.7	19.50
ANO06.001.41.001.00B	H05VV5-F	41 G 1.0	300/500V	35/0.19	26.2	886	19.50
ANO06.001.03.001.50B	H05VV5-F	3 G 1.5	300/500V	31/0.25	9.4	109.8	13.30
ANO06.001.04.001.50B	H05VV5-F	4 G 1.5	300/500V	31/0.25	10.2	140.7	13.30
ANO06.001.05.001.50B	H05VV5-F	5 G 1.5	300/500V	31/0.25	11.4	175	13.30
ANO06.001.07.001.50B	H05VV5-F	7 G 1.5	300/500V	31/0.25	14.1	224.2	13.30
ANO06.001.12.001.50B	H05VV5-F	12 G 1.5	300/500V	31/0.25	17	361.7	13.30
ANO06.001.18.001.50B	H05VV5-F	18 G 1.5	300/500V	31/0.25	20.3	518.3	13.30
ANO06.001.25.001.50B	H05VV5-F	25 G 1.5	300/500V	31/0.25	24.3	729.9	13.30
ANO06.001.34.001.50B	H05VV5-F	34 G 1.5	300/500V	31/0.25	28.2	946.6	13.30
ANO06.001.03.002.50B	H05VV5-F	3 G2.5	300/500V	51/0.25	11.2	162.4	7.98
ANO06.001.04.002.50B	H05VV5-F	4 G2.5	300/500V	51/0.25	12.5	203.3	7.98
ANO06.001.05.002.50B	H05VV5-F	5 G2.5	300/500V	51/0.25	13.7	251.1	7.98
ANO06.001.07.002.50B	H05VV5-F	7 G2.5	300/500V	51/0.25	16.8	326	7.98
ANO06.001.12.002.50B	H05VV5-F	12 G2.5	300/500V	51/0.25	20.6	553.3	7.98
ANO06.001.14.002.50B	H05VV5-F	14 G2.5	300/500V	51/0.25	22.7	611	7.98



ANO06.001.18.002.50B	H05VV5-F	18 G2.5	300/500V	51/0.25	24.8	795.2	7.98
ANO06.001.25.002.50B	H05VV5-F	25 G2.5	300/500V	51/0.25	29.6	1,109.6	7.98

