



物料编号	规格	导体结构	外径下限 mm	外径上限 mm	近似重量 kg/km	导体电阻 Ω /km
ANO18.008.01.000.35B	1x0.35	22/0.14	1.2	1.4	5	54.4
ANO18.008.01.000.50B	1x0.50	18/0.19	1.4	1.6	6	37.1
ANO18.008.01.000.75B	1x0.75	27/0.19	1.7	1.9	9	24.7
ANO18.008.01.001.00B	1x1.00	35/0.19	1.9	2.1	11	18.5
ANO18.008.01.001.25B	1x1.25	25/0.25	2.1	2.3	12	14.9
ANO18.008.01.001.50B	1x1.50	31/0.25	2.2	2.4	17	12.7
ANO18.008.01.002.00B	1 x2.00	41/0.25	2.5	2.8	24	9.42
ANO18.008.01.002.50B	1 x2.50	51/0.25	2.7	3	28	7.6
ANO18.008.01.003.00B	1 x3.00	61/0.25	3.1	3.4	34	6.15
ANO18.008.01.004.00B	1 x4.00	82/0.25	3.4	3.7	44	4.71
ANO18.008.01.005.00B	1 x5.00	102/0.25	3.9	4.2	50	3.94
ANO18.008.01.006.00B	1 x6.00	123/0.25	4	4.3	64	3.14
ANO18.008.01.008.00B	1 x8.00	64/0.4	4.6	5	82	2.38
ANO18.008.01.010.00B	1 x10.00	77/0.4	5.4	5.8	113	1.82
ANO18.008.01.012.00B	1 x12.00	96/0.4	5.8	6.5	120	1.52
ANO18.008.01.016.00B	1 x16.00	126/0.4	6.5	7	171	1.16
ANO18.008.01.020.00B	1 x20.00	159/0.4	7	7.8	192	0.955
ANO18.008.01.025.00B	1 x25.00	189/0.4	7.9	8.7	255	0.743