



物料编号	型号	额定电压	规格	导体结构	电缆近似外径 mm	近似重量 kg/km	导体电阻Ω/km
AN011.001.01.002.50B	NYM	300/500V	1X2.5	51/0.25	6.3	82.5	4.95 Ω/km
AN011.001.01.004.00B	NYM	300/500V	1X4	82/0.25	7.2	116.1	3.30 Ω/km
AN011.001.01.006.00B	NYM	300/500V	1X6	123/0.25	7.6	146.4	1.91 Ω/km
AN011.001.01.010.00B	NYM	300/500V	1X10	77/0.4	9.1	227.7	1.21 Ω/km
AN011.001.01.016.00B	NYM	300/500V	1X16	126/0.4	10.1	318.7	0.780 Ω/km
AN011.001.03.001.50B	NYM	300/500V	3X1.5	31/0.25	8.9	173.3	10.64 Ω/km
AN011.001.04.001.50B	NYM	300/500V	4X1.5	31/0.25	9.6	210.5	10.64 Ω/km
AN011.001.05.001.50B	NYM	300/500V	5X1.5	31/0.25	10.4	254.3	10.64 Ω/km
AN011.001.07.001.50B	NYM	300/500V	7X1.5	31/0.25	12.1	336.9	10.64 Ω/km
AN011.001.03.002.50B	NYM	300/500V	3X2.5	51/0.25	10	245.2	4.95 Ω/km
AN011.001.04.002.50B	NYM	300/500V	4X2.5	51/0.25	11.2	310.9	4.95 Ω/km
AN011.001.05.002.50B	NYM	300/500V	5X2.5	51/0.25	12	372.7	4.95 Ω/km
AN011.001.07.002.50B	NYM	300/500V	7X2.5	51/0.25	14.2	501.2	4.95 Ω/km
AN011.001.03.004.00B	NYM	300/500V	3X4	82/0.25	11.8	357.2	3.30 Ω/km
AN011.001.04.004.00B	NYM	300/500V	4X4	82/0.25	13.3	456.7	3.30 Ω/km
AN011.001.05.004.00B	NYM	300/500V	5X4	82/0.25	14.5	556.9	3.30 Ω/km
AN011.001.03.006.00B	NYM	300/500V	3X6	123/0.25	13.3	478.3	1.91 Ω/km
AN011.001.04.006.00B	NYM	300/500V	4X6	123/0.25	14.3	586.7	1.91 Ω/km
AN011.001.05.006.00B	NYM	300/500V	5X6	123/0.25	16.1	737.2	1.91 Ω/km
AN011.001.04.010.00B	NYM	300/500V	4X10	77/0.4	18.6	988.9	1.21 Ω/km
AN011.001.05.010.00B	NYM	300/500V	5X10	77/0.4	20	1194.8	1.21 Ω/km
AN011.001.05.016.00B	NYM	300/500V	5X16	126/0.4	23.9	1759.7	0.780 Ω/km
AN011.001.04.025.00B	NYM	300/500V	4X25	189/0.4	26.9	2199.5	0.554 Ω/km
AN011.001.05.025.00B	NYM	300/500V	5X25	189/0.4	28.9	2659.2	0.554 Ω/km